-2-

## AMENDMENT TO THE CLAIMS

## 1-14. (canceled)

- 15. (previously presented) A method of forming an identification card comprising steps of:
  - a) providing an ink-receptive material that includes a backing layer and an ink-receptive coating on a surface of the backing layer;
  - b) providing a card member;
  - c) laminating the ink-receptive material to a surface of a card member such that the ink-receptive coating is bonded to the surface of the card member
  - d) removing the backing layer from the ink-receptive coating; and
  - e) printing an image to a surface of the ink-receptive coating following the removing step.

## 16-19. (canceled).

- 20. (previously presented) The method of claim 15, wherein the laminating step c) includes applying heat and pressure to the ink-receptive material and the card member.
- 21. (previously presented) The method of claim 15, wherein the ink-receptive material overhangs edges of the card member during the laminating step c).
- 22. (original) The method of claim 15, wherein the ink-receptive material is in the form of an individual ink-receptive sheet.
- 23. (previously presented) The method of claim 22, wherein the ink-receptive sheet completely covers the surface of the card substrate during the laminating step c).
- 24. (original) The method of claim 15, wherein the ink-receptive material is in the form of an ink-receptive film.

-3-

- 25. (original) The method of claim 24, wherein the ink-receptive film is supported on a supply roll.
- 26. (original) The method of claim 15, wherein the card member is sized in accordance with standardized identification card substrates.
- 27. (original) The method of claim 15, wherein the card member is in the form of a sheet of card substrate material.
- 28. (previously presented) The method of claim 27 including cutting an identification card substrate from the sheet of card substrate material following the laminating step c).
- 29. (original) The method of claim 15, wherein the card member includes an embedded chip having exposed contacts.
- 30. (previously presented) The method of claim 29, wherein the ink-receptive coating does not bond to the exposed contacts during the laminating step c).
- 31. (previously presented) A device for forming a card substrate comprising:
  - a supply of ink-receptive material having a backing layer and an ink-receptive coating on the surface of the backing layer;
  - a laminating section configured to laminate the ink-receptive material to a surface of a card member, wherein the ink-receptive coating is bonded to and completely covers the surface of the card member; and
  - a separator configured to remove the backing layer of the ink-receptive material from the ink-receptive coating and the card member.

4-

- 32. (original) The device of claim 31, wherein the laminating section includes a heated roller.
- 33. (original) The device of claim 31, wherein the supply of ink-receptive material includes at least one ink-receptive sheet.
- 34. (original) The device of claim 33 including a sheet feed mechanism configured to transport individual ink-receptive sheets from the supply of ink-receptive material to the laminating section.
- 35. (original) The device of claim 31, wherein the supply of ink-receptive material includes an ink-receptive film contained on a supply roll.
- 36. (original) The device of claim 35, wherein the laminating section includes a heated roller and the ink-receptive film is fed between the heated roller and the card member.
- 37. (original) The device of claim 31, including a card supply containing a plurality of card members and a card feed mechanism configured to transport individual card members to the laminating section.
- 38. (original) The device of claim 31, wherein the card member is sized in accordance with an identification card substrate.
- 39. (original) The device of claim 31, wherein the card member is a sheet of identification card substrate material.
- 40. (original) The device of claim 31 including a printhead configured to receive the ink-receptive material and print an image on the ink-receptive coating.

-5-

- 41. (original) The device of claim 40, wherein the printhead is an ink jet printhead.
- 42. (canceled)
- 43. (previously presented) The device of claim 31, wherein the separator includes at least one peeling wedge.
- 44. (previously presented) The device of claim 31, wherein the separator includes a peeling roller that directs the ink-receptive material away from the ink-receptive coating bonded to the card member at an acute angle relative to the card member.
- 45. (original) The device of claim 44, wherein an axis of rotation of the peeling roller is at an acute angle relative to a direction in which the card member travels.
- 46. (previously presented) The method of claim 1 including printing an image on the ink-receptive coating before laminating the ink-receptive material to a surface of the card member.
- 47. (previously presented) The method of claim 15, wherein the ink-receptive coating is in contact with the surface of the backing layer in step (a).
- 48. (previously presented) The method of claim 15, wherein the ink-receptive coating completely covers the surface of the card member in step (c).
- 49. (previously presented) The method of claim 15, wherein the ink receptive coating is in contact with the surface of the backing layer in step (a) and the ink-receptive coating completely covers the surface of the card member in step (c).